



Crown Acoustic Partition Roll

Description

Crown Acoustic Partition Roll is a flexible, resilient, unfaced roll of glass mineral wool. It is supplied in dimensions to suit studs at standard 600mm centres.

Application

Crown Acoustic Partition Roll is designed specifically for the sound insulation of metal and timber stud partitions.

Using mineral wool as a sound absorbent layer in partitions will significantly improve their acoustic performance, whilst only adding minimally to the overall mass of the structure.

The mineral wool complements the plasterboard by absorbing airborne sound in the cavity and reducing reverberation. It also has the effect of reducing the hollow sound that can occur in partitions with unfilled cavities.

Metal stud partitions faced with standard 12.5mm plasterboard and infilled with Crown Acoustic Partition Roll can meet the requirement for a 40 R_w dB sound reduction in accordance with Approved Document E of the Building Regulations.

Product Data

Thickness	Length	Width	Area per pack
(mm)	(m)	(mm)	(m ²)
100	6.50	2 x 600	7.80
75	7.00	2 x 600	8.40
50	13.00	2 x 600	15.60
25	10.00	4 x 600	24.00

All dimensions are nominal

Performance

Acoustic

Crown Acoustic Partition Roll has exceptional acoustic absorption properties.

Fire

Crown Acoustic Partition Roll is classified as Euroclass A1 to BS EN ISO 13501-1.

Benefits

- Excellent sound absorption
- Dimensioned to suit 600mm stud centres
- Quick, economic installation
- Can be used with standard plasterboard to achieve a sound reduction of 40 R_w dB
- Friction fits between studs, ensuring continuity of the absorbent layer with no gaps



Standards

Crown Acoustic Partition Roll is a non-combustible, inorganic glass wool, defined as mineral wool in BS 3533: 1981 and is manufactured in accordance with BSI Quality Assurance Standard BS EN ISO 9001: 2000

Durability

Crown Acoustic Partition Roll is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Environmental

Crown Acoustic Partition Roll is free from CFCs, HCFCs and any other material with ozone depletion potential in its manufacture and content and represents no known threat to the environment.

Crown Acoustic Partition Roll's manufacture has a low impact on the environment and is classified as Zero ODP and Zero GWP.

Vapour Resistivity

Crown Acoustic Partition Roll has a vapour resistivity of 7.00 MN.s.g.m.

Handling and Storage

Crown Acoustic Partition Roll is easy to handle and install, being lightweight and easily cut to size.

It is supplied enclosed in polythene which is designed for short term protection only. For longer term protection on site, the product should be stored either indoors, or under cover and off the ground. Installation instructions are on every pack.

Crown Acoustic Partition Roll should not be left permanently exposed to the elements.

Knauf Insulation Ltd
PO Box 10, Stafford Road,
St Helens, Merseyside,
WA10 3NS

Customer Service (Sales) Tel: 0844 800 0135
Technical Advisory Centre Tel: 01744 766666
Literature Tel: 08700 668660
www.knaufinsulation.co.uk

For more information please refer to
www.knaufinsulation.co.uk

Ref: CD86507

