



Storage, Installation and Handling

Celotex
Insulation Specialists

Storage

- Celotex insulation boards should be stored dry, flat and clear of the ground. Only as much material as can be installed during a single working period should be removed from storage at any one time. If boards are stored under tarpaulins, care should be taken to prevent rope damage to boards.

Installation

- Always install Celotex insulation boards in accordance with the instructions supplied by Celotex.
- Celotex insulation boards should not be installed when the temperature is at or below 4°C and falling.
- Where possible, cut the product using the Celotex Insulation Saw to minimise dust creation.
- When cutting Celotex insulation, dust extraction equipment, eye protection and face masks should be provided. Dust or particles in the eyes should be washed out with liberal quantities of water. If skin is sensitive to fibre irritation, apply a barrier cream to exposed areas before handling.

Handling

- Care should also be taken to ensure that packs are not dropped on to corners or edges.
- Aluminium foil edges may be sharp. Avoid sliding bare hands along board edges.

Other Information

Intended use: Thermal insulation of building structures as described in Celotex product literature.

COSHH - Under the COSHH Regulations 2002, it is the duty of employers to prevent or control the exposure of their employees to substances hazardous to health. Man-made mineral fibres (including glass fibres) are subject to maximum exposure limit (MEL) as defined in HSE Guidance Note EH40.

Further Information

If you wish to contact Celotex, please visit celotex.co.uk and click on the 'contact us' page.

Celotex has a policy of continuous product development and reserves the right to alter product designs or specifications without prior notice.